

BIOSECURITY GATE 5+

- **WATER CONSUMPTION:** from 30 l/min up to 130l/min
- Chemical solution consumption (water + chemicals) 15l-35l/truck
- **DISINFECTION TIME:** 15-25 sek/ truck
- **DISINFECTION FRAME:** powder coated aluminum
- Disinfection frame widened to a maximum of 12 m in width
- Stainless or PVC spraying system
- 9 - 13 nozzles undercarriage spraying system
- Equipped with a 230V or 400V powered pump
- Automatic chemical dilution
- 27 - 48 pcs spray nozzles, different types
- 25m hose for spraying in inaccessible spots
- **REMOTE CONTROL:** start/stop function
- **VEHICLE DETECTORS AND REMOTE CONTROLLERS:** Automatic start/stop function - Vehicle detectors and remote controllers
- Manual start push button
- **HEATING:** a heating system with built-in thermostat that starts heating when the temperature drops below 0°C
- **STORAGE:** Component Storage keeps inside pumps, chemical containers, control panel, dilution systems, etc.
- **LARGE STORAGE:** Component Storage keeps inside 600l clean water tank, pumps, chemical containers, control panel, dilution systems, etc.
- Night visibility elements
- **COLOR:** yellow or made to order
- **DIMENSION:** High 500cm x Width - can be made with any size



BIOSECURITY GATE 5+

A device with an extended width, enabling the passage of all kinds of vehicles. Device for disinfecting vehicles entering the property. 360 ° vehicle disinfection.



CHEMICAL DILUTION RATE

Tip No.	1	2	3	4	5	6	7	8	9	10	11	No Tip	
% solution	0,3	0,5	0,8	1	1,3	1,5	1,5	2	2,5	3	5	7	14